

- 1 -

FILE CONVERSION METHOD, FILE CONVERTER, AND
FILE DISPLAY SYSTEM

BACKGROUND OF THE INVENTION

1. Field of the Invention

The present invention relates to a file conversion method, a data converter, and a file display system for extracting data, which can be handled by a device having a limited display capability, from a file composed of a plurality of pieces of data displayable on a display unit with a start and an end of each piece of data indicated by respective identifiers and for outputting the extracted data to the limited-capability device.

2. Description of the Related Art

The network called the Internet is now in widespread use, and users have an easy access to a diversity of information through personal computers over the Internet. Information the user monitors using a software program called Web browser is described in the HTML (HyperText Markup Language).

The HTML document is associated with an identifier called tag. The tag determines the structure of each document. Specifically, when the user monitors a HTML document using the Web browser, the font, the size, and the color of a text, and the location of an image file are described by the tag. The tag determines the structure of the text information and image information on a Web page monitored by the user.

The use of mobile terminals becomes widespread, and the user has an immediate access to various pieces of information in transit or at a destination of a travel. To gain access to desired information on a mobile terminal, the user needs to input information on the mobile terminal. As a means for collecting information to the mobile terminal, the user may use a personal computer. The user connects the mobile terminal to the personal computer to download the desired information to the mobile terminal.

When a user transmits, to a mobile terminal, Web page information which has been obtained to a personal computer from a particular server, it is necessary to reorganize the information into data displayable on the mobile terminal and then transmit the data to the mobile terminal. The user must select required data from unnecessary data, and transmit the required data only. Further, the user must reorganize the extracted data in a size and format displayable or easy to see on the mobile terminal. The user is therefore forced to perform a variety of jobs from acquiring home page data to transmitting the reorganized data to the mobile terminal.

Although the Web pages provided over the Internet are written in the HTML, their formats are diversified. Specifically, the contents provided by the servers are varied in HTML document structure from server to server. The user is forced to use different extraction methods and different shaping

methods from content to content to reorganize the data for the mobile terminal.

When the user uses a browser, a home page service on the network may be preregistered as a bookmark on the computer.

Since the bookmark is stored in the URL (Uniform Resource Locator) or character strings, the user has difficulty identifying the content provided by the service at a glance.

SUMMARY OF THE INVENTION

It is an object of the present invention to provide a file conversion method, a data converter, and a file display system for extracting data handled by a device having a limited display capability from a plurality of pieces of data displayable on a display unit with a start and an end of each piece of data indicated by respective identifiers and for outputting the extracted data to the limited-capability device.

The present invention in one aspect relates to a file conversion method for extracting, from a file composed of a plurality of pieces of data displayable on a display unit and with a start and an end of each piece of data indicated by respective identifiers, data displayable on a limited-capability device, in accordance with the identifiers, and for outputting the extracted data to the limited-capability device. The file conversion method includes a step of detecting the identifier by reading the file, a step of determining whether

the limited-capability device can display the data indicated by the extracted identifier, a step of extracting the data, the start and the end of which are indicated by the determined identifier and which is determined to be displayable on the limited-capability device, and a step of outputting an output file which is newly created from the extracted data, as a different file from the first file.

13
14
15
16
17
18
19
20
21
22
23
24
25
26
27
28
29
30
31
32
33
34
35
36
37
38
39
40
41
42
43
44
45
46
47
48
49
50
51
52
53
54
55
56
57
58
59
60
61
62
63
64
65
66
67
68
69
70
71
72
73
74
75
76
77
78
79
80
81
82
83
84
85
86
87
88
89
90
91
92
93
94
95
96
97
98
99
100
101
102
103
104
105
106
107
108
109
110
111
112
113
114
115
116
117
118
119
120
121
122
123
124
125
126
127
128
129
130
131
132
133
134
135
136
137
138
139
140
141
142
143
144
145
146
147
148
149
150
151
152
153
154
155
156
157
158
159
160
161
162
163
164
165
166
167
168
169
170
171
172
173
174
175
176
177
178
179
180
181
182
183
184
185
186
187
188
189
190
191
192
193
194
195
196
197
198
199
200
201
202
203
204
205
206
207
208
209
210
211
212
213
214
215
216
217
218
219
220
221
222
223
224
225
226
227
228
229
230
231
232
233
234
235
236
237
238
239
240
241
242
243
244
245
246
247
248
249
250
251
252
253
254
255
256
257
258
259
260
261
262
263
264
265
266
267
268
269
270
271
272
273
274
275
276
277
278
279
280
281
282
283
284
285
286
287
288
289
290
291
292
293
294
295
296
297
298
299
300
301
302
303
304
305
306
307
308
309
310
311
312
313
314
315
316
317
318
319
320
321
322
323
324
325
326
327
328
329
330
331
332
333
334
335
336
337
338
339
340
341
342
343
344
345
346
347
348
349
350
351
352
353
354
355
356
357
358
359
360
361
362
363
364
365
366
367
368
369
370
371
372
373
374
375
376
377
378
379
380
381
382
383
384
385
386
387
388
389
390
391
392
393
394
395
396
397
398
399
400
401
402
403
404
405
406
407
408
409
410
411
412
413
414
415
416
417
418
419
420
421
422
423
424
425
426
427
428
429
430
431
432
433
434
435
436
437
438
439
440
441
442
443
444
445
446
447
448
449
450
451
452
453
454
455
456
457
458
459
460
461
462
463
464
465
466
467
468
469
470
471
472
473
474
475
476
477
478
479
480
481
482
483
484
485
486
487
488
489
490
491
492
493
494
495
496
497
498
499
500
501
502
503
504
505
506
507
508
509
510
511
512
513
514
515
516
517
518
519
520
521
522
523
524
525
526
527
528
529
530
531
532
533
534
535
536
537
538
539
540
541
542
543
544
545
546
547
548
549
550
551
552
553
554
555
556
557
558
559
560
561
562
563
564
565
566
567
568
569
570
571
572
573
574
575
576
577
578
579
580
581
582
583
584
585
586
587
588
589
590
591
592
593
594
595
596
597
598
599
600
601
602
603
604
605
606
607
608
609
610
611
612
613
614
615
616
617
618
619
620
621
622
623
624
625
626
627
628
629
630
631
632
633
634
635
636
637
638
639
640
641
642
643
644
645
646
647
648
649
650
651
652
653
654
655
656
657
658
659
660
661
662
663
664
665
666
667
668
669
670
671
672
673
674
675
676
677
678
679
680
681
682
683
684
685
686
687
688
689
690
691
692
693
694
695
696
697
698
699
700
701
702
703
704
705
706
707
708
709
710
711
712
713
714
715
716
717
718
719
720
721
722
723
724
725
726
727
728
729
730
731
732
733
734
735
736
737
738
739
740
741
742
743
744
745
746
747
748
749
750
751
752
753
754
755
756
757
758
759
760
761
762
763
764
765
766
767
768
769
770
771
772
773
774
775
776
777
778
779
780
781
782
783
784
785
786
787
788
789
790
791
792
793
794
795
796
797
798
799
800
801
802
803
804
805
806
807
808
809
810
811
812
813
814
815
816
817
818
819
820
821
822
823
824
825
826
827
828
829
830
831
832
833
834
835
836
837
838
839
840
841
842
843
844
845
846
847
848
849
850
851
852
853
854
855
856
857
858
859
860
861
862
863
864
865
866
867
868
869
870
871
872
873
874
875
876
877
878
879
880
881
882
883
884
885
886
887
888
889
890
891
892
893
894
895
896
897
898
899
900
901
902
903
904
905
906
907
908
909
910
911
912
913
914
915
916
917
918
919
920
921
922
923
924
925
926
927
928
929
930
931
932
933
934
935
936
937
938
939
940
941
942
943
944
945
946
947
948
949
950
951
952
953
954
955
956
957
958
959
960
961
962
963
964
965
966
967
968
969
970
971
972
973
974
975
976
977
978
979
980
981
982
983
984
985
986
987
988
989
990
991
992
993
994
995
996
997
998
999
1000
1001
1002
1003
1004
1005
1006
1007
1008
1009
1010
1011
1012
1013
1014
1015
1016
1017
1018
1019
1020
1021
1022
1023
1024
1025
1026
1027
1028
1029
1030
1031
1032
1033
1034
1035
1036
1037
1038
1039
1040
1041
1042
1043
1044
1045
1046
1047
1048
1049
1050
1051
1052
1053
1054
1055
1056
1057
1058
1059
1060
1061
1062
1063
1064
1065
1066
1067
1068
1069
1070
1071
1072
1073
1074
1075
1076
1077
1078
1079
1080
1081
1082
1083
1084
1085
1086
1087
1088
1089
1090
1091
1092
1093
1094
1095
1096
1097
1098
1099
1100
1101
1102
1103
1104
1105
1106
1107
1108
1109
1110
1111
1112
1113
1114
1115
1116
1117
1118
1119
1120
1121
1122
1123
1124
1125
1126
1127
1128
1129
1130
1131
1132
1133
1134
1135
1136
1137
1138
1139
1140
1141
1142
1143
1144
1145
1146
1147
1148
1149
1150
1151
1152
1153
1154
1155
1156
1157
1158
1159
1160
1161
1162
1163
1164
1165
1166
1167
1168
1169
1170
1171
1172
1173
1174
1175
1176
1177
1178
1179
1180
1181
1182
1183
1184
1185
1186
1187
1188
1189
1190
1191
1192
1193
1194
1195
1196
1197
1198
1199
1200
1201
1202
1203
1204
1205
1206
1207
1208
1209
1210
1211
1212
1213
1214
1215
1216
1217
1218
1219
1220
1221
1222
1223
1224
1225
1226
1227
1228
1229
1230
1231
1232
1233
1234
1235
1236
1237
1238
1239
1240
1241
1242
1243
1244
1245
1246
1247
1248
1249
1250
1251
1252
1253
1254
1255
1256
1257
1258
1259
1260
1261
1262
1263
1264
1265
1266
1267
1268
1269
1270
1271
1272
1273
1274
1275
1276
1277
1278
1279
1280
1281
1282
1283
1284
1285
1286
1287
1288
1289
1290
1291
1292
1293
1294
1295
1296
1297
1298
1299
1300
1301
1302
1303
1304
1305
1306
1307
1308
1309
1310
1311
1312
1313
1314
1315
1316
1317
1318
1319
1320
1321
1322
1323
1324
1325
1326
1327
1328
1329
1330
1331
1332
1333
1334
1335
1336
1337
1338
1339
1340
1341
1342
1343
1344
1345
1346
1347
1348
1349
1350
1351
1352
1353
1354
1355
1356
1357
1358
1359
1360
1361
1362
1363
1364
1365
1366
1367
1368
1369
1370
1371
1372
1373
1374
1375
1376
1377
1378
1379
1380
1381
1382
1383
1384
1385
1386
1387
1388
1389
1390
1391
1392
1393
1394
1395
1396
1397
1398
1399
1400
1401
1402
1403
1404
1405
1406
1407
1408
1409
1410
1411
1412
1413
1414
1415
1416
1417
1418
1419
1420
1421
1422
1423
1424
1425
1426
1427
1428
1429
1430
1431
1432
1433
1434
1435
1436
1437
1438
1439
1440
1441
1442
1443
1444
1445
1446
1447
1448
1449
1450
1451
1452
1453
1454
1455
1456
1457
1458
1459
1460
1461
1462
1463
1464
1465
1466
1467
1468
1469
1470
1471
1472
1473
1474
1475
1476
1477
1478
1479
1480
1481
1482
1483
1484
1485
1486
1487
1488
1489
1490
1491
1492
1493
1494
1495
1496
1497
1498
1499
1500
1501
1502
1503
1504
1505
1506
1507
1508
1509
1510
1511
1512
1513
1514
1515
1516
1517
1518
1519
1520
1521
1522
1523
1524
1525
1526
1527
1528
1529
1530
1531
1532
1533
1534
1535
1536
1537
1538
1539
1540
1541
1542
1543
1544
1545
1546
1547
1548
1549
1550
1551
1552
1553
1554
1555
1556
1557
1558
1559
1560
1561
1562
1563
1564
1565
1566
1567
1568
1569
1570
1571
1572
1573
1574
1575
1576
1577
1578
1579
1580
1581
1582
1583
1584
1585
1586
1587
1588
1589
1590
1591
1592
1593
1594
1595
1596
1597
1598
1599
1600
1601
1602
1603
1604
1605
1606
1607
1608
1609
1610
1611
1612
1613
1614
1615
1616
1617
1618
1619
1620
1621
1622
1623
1624
1625
1626
1627
1628
1629
1630
1631
1632
1633
1634
1635
1636
1637
1638
1639
1640
1641
1642
1643
1644
1645
1646
1647
1648
1649
1650
1651
1652
1653
1654
1655
1656
1657
1658
1659
1660
1661
1662
1663
1664
1665
1666
1667
1668
1669
1670
1671
1672
1673
1674
1675
1676
1677
1678
1679
1680
1681
1682
1683
1684
1685
1686
1687
1688
1689
1690
1691
1692
1693
1694
1695
1696
1697
1698
1699
1700
1701
1702
1703
1704
1705
1706
1707
1708
1709
1710
1711
1712
1713
1714
1715
1716
1717
1718
1719
1720
1721
1722
1723
1724
1725
1726
1727
1728
1729
1730
1731
1732
1733
1734
1735
1736
1737
1738
1739
1740
1741
1742
1743
1744
1745
1746
1747
1748
1749
1750
1751
1752
1753
1754
1755
1756
1757
1758
1759
1760
1761
1762
1763
1764
1765
1766
1767
1768
1769
1770
1771
1772
1773
1774
1775
1776
1777
1778
1779
1780
1781
1782
1783
1784
1785
1786
1787
1788
1789
1790
1791
1792
1793
1794
1795
1796
1797
1798
1799
1800
1801
1802
1803
1804
1805
1806
1807
1808
1809
1810
1811
1812
1813
1814
1815
1816
1817
1818
1819
1820
1821
1822
1823
1824
1825
1826
1827
1828
1829
1830
1831
1832
1833
1834
1835
1836
1837
1838
1839
1840
1841
1842
1843
1844
1845
1846
1847
1848
1849
1850
1851
1852
1853
1854
1855
1856
1857
1858
1859
1860
1861
1862
1863
1864
1865
1866
1867
1868
1869
1870
1871
1872
1873
1874
1875
1876
1877
1878
1879
1880
1881
1882
1883
1884
1885
1886
1887
1888
1889
1890
1891
1892
1893
1894
1895
1896
1897
1898
1899
1900
1901
1902
1903
1904
1905
1906
1907
1908
1909
1910
1911
1912
1913
1914
1915
1916
1917
1918
1919
1920
1921
1922
1923
1924
1925
1926
1927
1928
1929
1930
1931
1932
1933
1934
1935
1936
1937
1938
1939
1940
1941
1942
1943
1944
1945
1946
1947
1948
1949
1950
1951
1952
1953
1954
1955
1956
1957
1958
1959
1960
1961
1962
1963
1964
1965
1966
1967
1968
1969
1970
1971
1972
1973
1974
1975
1976
1977
1978
1979
1980
1981
1982
1983
1984
1985
1986
1987
1988
1989
1990
1991
1992
1993
1994
1995
1996
1997
1998
1999
2000
2001
2002
2003
2004
2005
2006
2007
2008
2009
2010
2011
2012
2013
2014
2015
2016
2017
2018
2019
2020
2021
2022
2023
2024
2025
2026
2027
2028
2029
2030
2031
2032
2033
2034
2035
2036
2037
2038
2039
2040
2041
2042
2043
2044
2045
2046
2047
2048
2049
2050
2051
2052
2053
2054
2055
2056
2057
2058
2059
2060
2061
2062
2063
2064
2065
2066
2067
2068
2069
2070
2071
2072
2073
2074
2075
2076
2077
2078
2079
2080
2081
2082
2083
2084
2085
2086
2087
2088
2089
2090
2091
2092
2093
2094
2095
2096
2097
2098
2099
2100
2101
2102
2103
2104
2105
2106
2107
2108
2109
2110
2111
2112
2113
2114
2115
2116
2117
2118
2119
2120
2121
2122
2123
2124
2125
2126
2127
2128
2129
2130
2131
2132
2133
2134
2135
2136
2137
2138
2139
2140
2141
2142
2143
2144
2145
2146
2147
2148
2149
2150
2151
2152
2153
2154
2155
2156
2157
2158
2159
2160
2161
2162
2163
2164
2165
2166
2167
2168
2169
2170
2171
2172
2173
2174
2175
2176
2177
2178
2179
2180
2181
2182
2183
2184
2185
2186
2187
2188
2189
2190
2191
2192
2193
2194
2195
2196
2197
2198
2199
2200
2201
2202
2203
2204
2205
2206
2207
2208
2209
2210
2211
2212
2213
2214
2215
2216
2217
2218
2219
2220
2221
2222
2223
2224
2225
2226

file stored in the file storage unit, for controlling the extractor unit to extract, as a new output file, data including the start and the end indicated by the identifier from the file, and for controlling the output unit to output the new output file to the limited-capability device.

The present invention in yet another aspect relates to a file conversion method for converting a file composed of a plurality of pieces of data displayable on a display unit with a start and an end of each piece of indicated by respective identifiers into data displayable on a connected limited-capability device, and outputting the data as a new output file to the limited-capability device. The file conversion method includes a step of initializing a first data buffer for buffering data when a plurality of pieces of data is read from the file, a step of detecting the identifier indicating the start of the data in the file, based on a rule for processing the data in the file into a data format displayable on the limited-capability device, when the data is from the file and is stored in the first data buffer, a step of moving the data stored in the first data buffer to a second data buffer for evacuation, a step of holding the data in the file, from the start thereof, into the first data buffer, based on the identifier indicating the start of the detected data, a step of detecting the identifier indicating the end of the data having the identifier indicating the end of the detected data, and a step of moving the data evacuated into the

second data buffer to the first data buffer for restoration.

The present invention in still another aspect relates to a file display system including a first apparatus for receiving a file including a plurality of pieces of data, displayable on a display unit, with the start and the end of each piece of data indicated by respective identifiers, and a second apparatus having a throughput lower than that of the first apparatus and receiving and displaying data into which the first apparatus converts the file. The first apparatus includes a storage unit for storing the file input thereto, a detector unit for detecting an identifier which indicates the data, which is processable by the second apparatus, from the file stored in the storage unit, an extractor unit for extracting, from the input file, the data which is detected by the detector unit and is processed into data processable by the second apparatus, a processing unit for processing the extracted data into the data that is processable by the second apparatus, an output unit for outputting the data, which has been processed to be processable by the second apparatus, to the second apparatus, and a control unit for controlling the storage unit to store the file input thereto in the storage unit, for controlling the detector unit to detect the identifier that indicates, from the file stored in the storage unit, data that can be processed to be processable by the second apparatus, for controlling the extractor unit to extract the data that is processed by the processing unit in

accordance with the identifier detected by the detector unit, and for controlling the output unit to output the data that has been processed by the processing unit. The second apparatus includes a receiver unit for receiving the data output by the first apparatus, and a display unit for displaying the data received by the receiver unit.

BRIEF DESCRIPTION OF THE DRAWINGS

FIG. 1 is a network diagram showing a preferred embodiment of an information processing apparatus of the present invention;

FIG. 2 is a block diagram showing the hardware structure of a preferred embodiment of the information processing apparatus of the present invention;

FIG. 3A is a perspective view of a mobile terminal which receives data from the information processing apparatus of the present invention;

FIG. 3B is a partial perspective view of the mobile terminal on a larger scale which receives data transmitted from the information processing apparatus of the present invention;

FIG. 4 is a block diagram showing the mobile terminal which receives data transmitted from the information processing terminal of the present invention;

FIG. 5A shows a first display state of a display screen of the mobile terminal which receives data from the information processing apparatus of the present invention;

FIG. 5B shows a second display state of the display screen of the mobile terminal which receives data from the information processing apparatus of the present invention;

FIG. 6 is a block diagram showing a preferred embodiment of the information processing apparatus of the present invention;

FIG. 7A shows the data structure of processing condition data in the information processing apparatus of the present invention;

FIG. 7B shows shaping conditions in detail of the data structure of the processing condition data in the information processing apparatus of the present invention;

FIG. 8A shows an initial state of in a shaping process in the information processing apparatus of the present invention;

FIG. 8B shows source data out of page data representing the shaping process in the information processing apparatus;

FIG. 8C shows a state subsequent to the shaping process in the information processing apparatus of the present invention;

FIG. 9 shows the data structure of a processing condition data area in the information processing apparatus of the present invention;

FIG. 10 shows one example of page data associated with a designated identifier in the information processing apparatus of the present invention;

FIG. 11A shows another example of page data associated with

a designated identifier in the information processing apparatus of the present invention;

FIG. 11B shows the result of shaping process performed on the page data associated with a designated identifier in the information processing apparatus of the present invention;

FIG. 12A shows another example of page data associated with a designated identifier in the information processing apparatus of the present invention;

FIG. 12B shows first text data that has been shaped from the example of page data associated with the designated identifier in the information processing apparatus of the present invention;

FIG. 12C shows second text data that has been shaped from the example of page data associated with the designated identifier in the information processing apparatus of the present invention;

FIG. 13 shows one example of page data associated with a designated identifier in the information processing apparatus of the present invention;

FIG. 14 shows a screen window in a preferred embodiment of the information processing apparatus of the present invention;

FIG. 15 is a flow diagram showing a preferred embodiment of the information processing method of the present invention;

FIG. 16 shows a screen window in a preferred embodiment of the information processing apparatus of the present invention;

FIG. 17 is a flow diagram showing a preferred embodiment of the information processing method of the present invention;

FIG. 18 is a flow diagram showing the processing of a designated identifier in the information processing method of the present invention;

FIG. 19 is a flow diagram showing the processing of a designated identifier in the information processing method of the present invention;

FIG. 20 is a flow diagram showing the processing of a designated identifier in the information processing method of the present invention;

FIG. 21 is a flow diagram showing the processing of a designated identifier in the information processing method of the present invention;

FIG. 22 is a flow diagram showing the processing of a designated identifier in the information processing method of the present invention;

FIG. 23 shows a screen window in the information processing method of the present invention;

FIG. 24A shows one example of a bitmap file generated in the information processing method of the present invention;

FIG. 24B shows one example of a first text file generated in the information processing method of the present invention;

FIG. 24C shows one example of a second text file generated in the information processing method of the present invention;

and

FIG. 25 shows a screen window in the information processing method of the present invention.

DESCRIPTION OF THE PREFERRED EMBODIMENTS

The embodiments of the present invention are now discussed, referring to the drawings. The following embodiments are illustrative only, and unless otherwise particularly described, the scope of the invention is not limited to these embodiments.

FIG. 1 is a network diagram showing a preferred embodiment of an information processing apparatus 20 of the present invention. The information processing apparatus 20 is now discussed, referring to FIG. 1. An information network 10 is connected to a plurality of servers 40, a client 50, and the information processing apparatus 20 to exchange data in a communication protocol such as the TCP/IP (Transmission Control Protocol/Internet Protocol). The server 40 stores a diversity of information to be provided to the client 50 and the information processing apparatus 20. The client 50 and the information processing apparatus 20 gain access to the server 40 to acquire information (data). The information network 10 is a wide-area network such the Internet or a LAN (Local Area Network). The information network 10 is constructed to provide the client with HTML documents of the WWW (World Wide Web).

The information processing apparatus 20 is a client

computer on the network, and is provided with a file monitor 200 called Web browser as shown in FIG. 6 as will be discussed later.

Using the file monitor 200, the client accesses a WWW server to acquire and monitor the data thereof. The information processing apparatus 20 has an external terminal to be connected to a mobile terminal 30, and can exchange data with the mobile terminal 30. The information processing apparatus 20 thus sends data stored therewithin to the mobile terminal 30, and further acquires the data stored in the mobile terminal 30.

FIG. 2 shows the hardware structure of a preferred embodiment of the information processing apparatus 20 of the present invention. The information processing apparatus 20 is now discussed, referring to FIG. 2. As shown, the information processing apparatus 20 is constructed of hardware resources of a personal computer, and includes a CPU (Central Processing Unit) 21, a memory 22, an auxiliary storage device 23, an input device 24, a display device 25, a network interface 26, and an external interface 27.

The CPU 21 reads software programs stored in the auxiliary storage device 23 or the memory 22 via a bus 28, and generally controls the operation of the information processing apparatus 20. The CPU 21 executes a variety of software programs stored in the auxiliary storage device 23 to be discussed later. The memory 22 forms a work area for the CPU 21, and temporarily stores software programs and data.

The auxiliary storage device 23 is a storage medium in a hard disk drive, a floppy disk drive, or an optical disk drive, and stores an OS (Operating System), application software programs, and a variety of data including page data PD, transmission data TD, and processing condition data PCD. The input device 24 is a keyboard or a mouse, for example. The user operates the input device 24, controlling the information processing apparatus 20 to execute a variety of software programs.

The display device 25 is a liquid-crystal display or a CRT (Cathode-Ray Tube) display, and has a display screen. A screen window is presented on the display screen when software programs to be discussed later are executed. The network interface 26 has a function of exchanging data between the information network 10 and the information processing apparatus 20. The network interface 26 may include a modem to be connected to the information network 10 through a telephone line or an Ethernet adaptor to be connected to the information network 10 through a proxy server.

The external interface 27 exchanges data with an external device, and may be an USB interface, an IEEE1394 interface, an infrared communication interface, or a Bluetooth interface, for example. The external interface 27 has an external connection terminal, to which the mobile terminal 30 is connected in a wired or wireless fashion. The transmission data TD may be exchanged

between the information processing apparatus 20 and the mobile terminal 30. The bus 28 is a signal line that permits information to be conveyed between devices constituting the information processing apparatus 20. Through the bus 28, data is internally exchanged in the information processing apparatus 20.

FIG. 3A is a perspective view of the mobile terminal 30.

Referring to FIGS. 3A and 3B, the mobile terminal 30 is now discussed. As shown, the mobile terminal 30 has a flat configuration, and has, on the front thereof, a display unit 31 formed of a liquid-crystal display panel. The display unit 31 has elongated projections 37a and 37b along the longitudinal edges thereof so that the display unit 31 is protected from a damage in the event of a fall, for example. Referring to FIG. 3A, a knob 32 and a power switch 33 are arranged on a left side panel 38a of a body 37. With the knob 32 and the power switch 33 mounted on the left side panel 38a, the left hand is used to operate the knob 32 and the power switch 33 with the mobile terminal 30 held in the left hand with the display unit 31 facing toward the user.

The knob 32 controls the operation of the mobile terminal 30. Operating the knob 32, the user displays predetermined information on the display unit 31. Specifically, the knob 32 is rotatable in the direction represented by an arrow R, and is pressed in the direction represented by an arrow P. The user rotates the knob 32 in the direction R to select transmission

data TD to be displayed, and presses the knob 32 in the direction of the arrow P to cause the display unit 31 to display the transmission data TD. The power switch 33, a slide switch, controls the power for ON/OFF operation.

An external terminal 93, not shown in FIGS. 3A and 3B, is arranged on a right side panel 38b, diametrically opposite to the side of the knob 32. The external terminal 93 constitutes an interface for exchanging data with the information processing apparatus 20 shown in FIG. 1. The external terminal 93 performs communication via a wired link, a wireless link, or an infrared link, for example, and is formed of a USB terminal, an IEEE1394 terminal, or a radio communication interface antenna of Bluetooth. Referring to FIG. 3B, controls 34, 35 and 36 are arranged on the top end face 39 of the body 37. The controls 34, 35, and 36 control the back light for the display unit 31 for an ON/OFF operation, and control the operation mode of the mobile terminal 30.

FIG. 4 is a block diagram showing the construction of the mobile terminal 30. The mobile terminal 30 is discussed, referring to FIG. 4. As shown, an external terminal controller 91 exchanges data with an external device connected to the external terminal 93 under the control of a CPU (Central Processing Unit) 92. A display controller 94 contains a VRAM (Video Random Access Memory) 94a, and displays a desired image by driving the display unit 31 in accordance with the content

in the VRAM 94a. Under the control of the CPU 92, a driver circuit 95 drives a back light 95a. The back light 95a illuminates the display unit 31. The user operates the control 36, thereby controlling the operation of the driver circuit 95.

A storage unit 96 is fabricated of a flash memory, and stores a variety of software programs required by the CPU 92 for the operation thereof while storing the transmission data TD sent from the information processing apparatus 20. The transmission data TD in the storage unit 96 has a directory structure, and each directory stores files with the content thereof falling within the category of the directory.

The programs stored in the storage unit 96 include a transmission data processing program that processes the transmission data TD sent from the information processing apparatus 20 and displays the processed transmission data TD on the display unit 31. The transmission data processing program processes a predetermined data format only. By restricting processable data formats, hardware resources are simplified and the mobile terminal 30 is thus miniaturized with a flat design implemented.

The predetermined data formats may be text data for text information and bitmap data for image information. The transmission data TD is organized in files of text data or bitmap data. The text data refers to a file containing character data and limited control codes such as the one for line feed. The

bitmap data refers to image data that is expressed by a set of points.

FIGS. 5A and 5B are plan views showing examples of the display screen of the mobile terminal 30. The screen of the display unit 31 displays the content of the storage unit 96 which is provided by the CPU 92 when the CPU 92 executes a processing program. FIG. 5A shows a main screen when the mobile terminal 30 is switched on. As shown, the top portion of the display unit 31, serving as an index display area ARA, displays the name of this mobile terminal 30 and a file name of text data or bitmap data. A battery mark M361 is presented on the right hand side portion of the index display area ARA. The battery mark M361 indicates a remaining battery power with the black area thereof varying depending on a battery status. The user thus monitors the remaining battery power.

An operation mark M362 is presented on the right of the battery mark M361. The operation mark M362 indicates the direction in which the knob 32 is rotatable. The user recognizes the operational state of the knob 32 at a glance. This provides a good user interface in operation.

A data display area ARM is presented below the index display area ARA. The data display area ARM displays the transmission data TD stored in the storage unit 96 of the mobile terminal 30 in a tree structure. The data display area ARM also displays the text data and the bitmap data in the storage unit 96, as shown

in FIG. 5B. Viewing the data display area ARM, the user monitors the content of the transmission data TD.

The data display area ARM in FIG. 5A presents a variety of setting items for the mobile terminal 30, which is treated as a virtual folder, in a tree structure. For example, the setting items include System for this mobile terminal 30 user's personal information, History holding a record of displayed file names, Star mark being a virtual folder containing files marked by the user, Heart mark, Checkmark, and Set/information in which various settings are performed.

A select item display area ARB is provided on the bottom portion of the display unit 31. The select item display area ARB displays an item selected by a cursor K in the data display area ARM. Referring to FIG. 5B, the select item display area ARB is not displayed when the data display area ARM presents the content of a file on the screen.

The operation of the mobile terminal 30 is now discussed, referring to FIG. 3A through FIG. 5B. As shown in FIG. 3A, the power switch 33 is operated to switch on the mobile terminal 30. The screen appears on the display unit 31 as shown in FIG. 5A. Manipulating the knob 32, the user moves the cursor K within the display unit 31 to select a directory that stores the transmission data TD to be displayed.

When the user presses the knob 32 in the direction of the arrow P, the information of the selected directory appears in

a tree structure. The user moves the cursor K within the directory using the knob 32, places the cursor K on a file to be displayed, and presses the knob 32. Referring to FIG. 5B, the transmission data TD is displayed on the data display area ARM.

FIG. 6 is a block diagram showing a preferred embodiment of the information processing apparatus of the present invention.

The information processing apparatus 20 is discussed, referring to FIG. 6. As shown, the information processing apparatus 20 is generally controlled by the CPU 21 which works in accordance with information processing programs stored in the hard disk.

Available as media for storing programs to be installed in a computer for execution are not only removable package media such as a floppy disk, a CD-ROM, and a DVD, but also a semiconductor memory and a magnetic disk into which programs are temporarily or permanently stored. Means for storing programs in a program storing medium may be a wired communication system or a wireless communication system such as a local area network, the Internet, or a digital broadcasting satellite. A variety of communication interfaces such as a router and a modem may be used between the communication system and the information processing apparatus 20.

Referring to FIG. 6, the information processing apparatus 20 includes a data converter 101, a transmission unit 102, a processing controller 111, a page data acquisition unit 112, and

a page data shaping unit 113. The data converter 101 converts data in a variety of formats stored in a data area 23a of the auxiliary storage device 23 into the transmission data TD in a format displayable on the mobile terminal 30. For example, the data of a HTML document resulting from an electronic mail, an address book, schedule, maps, and an automatic Web page download program is converted into text data or bitmap data by the data converter 101.

The transmission unit 102 has the function of transmitting the transmission data TD stored in a transmission data area 103 to the mobile terminal 30. The transmission unit 102 has also the function of receiving the transmission data TD from the mobile terminal 30 through the external interface 27 shown in FIG. 2 and the external terminal 93 shown in FIG. 4 and storing the received transmission data TD in the transmission data area 103. The transmission data TD transmitted from the transmission unit 102 can be monitored on the mobile terminal 30, while the transmission data TD transmitted from the mobile terminal 30 can be monitored on the information processing apparatus 20.

The transmission data area 103, storing the transmission data TD, is formed in the auxiliary storage device 23. In the transmission data area 103, the transmission data TD is arranged in a tree structure with the text files or the bitmap files in a directory. The data converter 101 and the page data shaping unit 113 to be discussed later are used to create a directory

in the transmission data area 103 and store the text data or the bitmap data in the created directory. The transmission data TD is stored in a manner such that each file is held in a respective directory which is created corresponding to the category of the file. Viewing the directory, the user immediately learns which category the transmission data TD belongs to. In this way, the user interface of the information processing apparatus 20 is enhanced.

The processing controller 111 has the function of calling the processing condition data PCD stored in a processing condition data area 114, and sending the processing condition data PCD to the page data shaping unit 113 to be discussed later.

Specifically, when the user clicks a service icon SA, the processing controller 111 recognizes a clicked service identifier 403. The processing controller 111 acquires the processing condition data PCD from the processing condition data area 114 according to the service identifier 403. The processing controller 111 sends address information 407 in the processing condition data PCD to the file monitor 200 while sending the address information 407 to the page data shaping unit 113 at the same time. The processing condition data area 114 is formed in the hard disk drive in the auxiliary storage device 23 shown in FIG. 2.

As will be discussed later, the processing controller 111, connected to a processing condition data server 11, updates the

processing condition data PCD or adds new processing condition data PCD in the processing condition data area 114. The processing controller 111 starts up the file monitor 200 and displays an acquired icon AA to be discussed later.

Referring to FIGS. 7A and 7B, the processing condition data PCD includes file information 401, category information 402, the service identifier 403, a service name 404, icon information 405, directory information 406, the address information 407, shaping conditions 408, etc. The file information 401 includes information about the date of creation of the processing condition data PCD, the date of update of the processing condition data PCD, a file version number, etc. The category information 402 indicates the service content provided by the processing condition data PCD. Based on the category information 402, the processing condition data PCD is stored in a predetermined location in the processing condition data area 114. Network servers on the information network 10 are respectively tagged with their own service identifiers 403. The service name 404 is derived from the service provided by that network server.

The icon information 405 is image information for use in the service icon SA and the acquired icon AA, as will be discussed later. The directory information 406 is local address information according to which the page data shaping unit 113 creates a directory in the transmission data area 103. The

address information 407 is an address of a network server providing service, for example, a URL. The shaping conditions 408 are conditions under which the page data shaping unit 113 shapes the page data PD. Based on these pieces of information, the processing controller 111 and the page data shaping unit 113 shape the page data PD.

Referring to FIG. 7B, the shaping conditions 408 include format conditions 408a, tag analysis conditions 408b, and imaging conditions 408c. The format conditions 408a include a character count per line condition defining a character count per line in shaped text data, and a line boundary character condition setting a character that is prohibited from being positioned at the start of a line or the end of the line. The format conditions 408a also include file conditions that set the type of image data of an image contained in the page data PD, for example, JPEG, GIF, etc.

The tag analysis conditions 408b are used to analyze the tag structure of the page data PD in the shaping of the page data PD. When a table shown in FIG. 8A is inserted into the page data PD, the source of the page data PD is something like the one shown in FIG. 8B. The tag analysis conditions 408b are so set that a new line begins at a <TR>...<TR> tag and that another new line begins at a <TD> tag. In the shaped text data shown in FIG. 8C, a line begins at each cell. In this way, page data PD that is displayed in a particular format under the control of tag is

automatically laid out and shaped in text data.

The imaging conditions 408c include, in the shaped bitmap data, an image size condition for setting the maximum file size of bitmap data, an image width condition for setting the minimum image width, and an image height condition for setting the minimum image height. The imaging conditions 408c set the size of the bitmap data displayable on the display unit 31 of the mobile terminal 30.

Referring to FIG. 9, the processing condition data area 114 has a data structure containing a plurality of categories CY, each storing a plurality of pieces of processing condition data PCD. Specifically, the processing condition data server 11 creates categories CY1-CY4 having contents for restaurants, automobiles, computers, travels, for example. The category CY can be a directory, for example. The categories CY1-CY4 store the processing condition data PCD corresponding to the network servers assigned thereto. For example, if the category CY1 is for the computer field, the category CY1 corresponds to network servers of computer software firms and computer hardware firms, for example, and stores processing condition data PCDa1-PCDa4. The determination of the category CY is performed by the processing controller 111 according to the category information 402 in the processing condition data PCD.

The processing condition data PCD is stored according to the category CY. As will be discussed later, to select the

processing condition data PCD to be used, the user selects the category first, and selects the processing condition data PCD. The user can register desired service with ease, and user interface is improved.

The page data acquisition unit 112 acquires the page data PD displayed on the file monitor 200, and sends the page data PD to the page data shaping unit 113. The file monitor 200, a so-called browser, is a computer application software for browsing the page data PD that can be accessed over a global network such as the Internet or a local network. The page data PD is compatible with a format such as HTML, SGML (Standard Generalized Markup Language), or XML (eXtensible Markup Language), and includes a control character called a tag. The file monitor 200 includes a cache area 201 for temporarily storing the browsed page data PD. The cache area 201 is formed in the hard disk in the auxiliary storage device 23.

The page data acquisition unit 112 searches for the page data PD currently displayed on the file monitor 200 referring to the page data PD stored in the cache area 201 of the file monitor 200. This searching operation is performed based on the address AS of the page data PD displayed on the file monitor 200. The address AS indicates the location of the page data PD over the network, and can be a URL (Uniform Resource Locator), for example. The page data acquisition unit 112 sends the page data PD in the cache area 201 to the page data shaping unit 113.

Specifically, the page data acquisition unit 112 acquires, from the cache area 201 of the auxiliary storage device 23, the page data PD already monitored with the information processing apparatus 20 connected to the network. Even in its unconnected state with the network, the page data PD currently viewed is monitored again. As will be discussed later, the user shapes the page data PD after viewing the page data PD, and determining whether to shape the page data PD.

The page data shaping unit 113 shapes the page data PD sent from the page data acquisition unit 112 based on the processing condition data PCD to display the page data PD on the mobile terminal 30. When the page data PD is a HTML document, for example, the page data PD may include text data, image data, banner advertisements, scripts, backgrounds, etc. The form of the text data and the size of the image data are different from page data to page data.

Analyzing the page data PD, the page data shaping unit 113 extracts data to be transmitted to the mobile terminal 30, such as text data and image data, in accordance with the processing condition data PCD. Specifically, the page data shaping unit 113 removes unnecessary data such as the banner advertisements.

The page data shaping unit 113 organizes the text data portion of the extracted page data PD into a text file. In the extraction of the data, the page data shaping unit 113 recognizes a designated identifier STG attached to the page data PD, and

determines the type of the data delimited by the designated identifiers STG.

The designated identifiers STG include a <GETINFO> tag and a </GETINFO> tag for delimiting a data shaping area, a <DUMPINFO> tag and a </DUMPINFO> tag for delimiting an unnecessary data area, a <IC_INDEX> tag and a </IC_INDEX> tag for indicating data index information, and a <COUPON> tag and a </COUPON> tag for indicating coupon information.

The <GETINFO> tag and the </GETINFO> tag are located at the ends of the transmission data TD to be acquired. For example, in the page data PD shown in FIG. 10, the page data shaping unit 113 analyzes the data between the <GETINFO> tag and the </GETINFO> tag, and recognizes the data as the data to be shaped.

The <GETINFO> tag permits a "name" parameter and a "link" parameter to be designated. The "name" parameter designates a name when the range delimited by the <GETINFO> tag and the </GETINFO> tag is shaped. The "link" parameter designates a link to another file in the shaped file.

The <DUMPINFO> tag and the </DUMPINFO> tag designate an unnecessary data area in need of no shaping process in the page data PD. In the page data PD shown in FIG. 11A, for example, the page data shaping unit 113 recognizes the data delimited by the <DUMPINFO> tag and the </DUMPINFO> tag as a range in need of no shaping, and performs no tag analysis for HTML. If the <GETINFO> tag and the </GETINFO> tag are set up, there is no need

for designating an unnecessary data range. However, when the unnecessary data range is extremely large, the use of the <DUMPINFO> tag and the </DUMPINFO> tag shortens the process involved. FIG. 11B shows an actual shaping result of the description shown in FIG. 11A. The file name actually shaped is "Samplefile.txt", and the data delimited by the <DUMPINFO> tag and the </DUMPINFO> tag, namely, the message "This range is not acquired" is not present after the shaping process as shown in FIG. 11B.

The <IC_INDEX> tag and the </IC_INDEX> tag indicate the type of data and individual information expressed in the page data PD. When the <IC_INDEX> tag and the </IC_INDEX> tag are included within the range delimited by the <GETINFO> tag and the </GETINFO> tag, the data between the <IC_INDEX> tag and the </IC_INDEX> tag is extracted to form a single file. In this case, a file formed by the <GETINFO> tag and the </GETINFO> tag excludes the data delimited between the <IC_INDEX> tag and the </IC_INDEX> tag. Like the <GETINFO> tag, the </IC_INDEX> tag permits a "name" parameter and a "link" parameter to be designated.

In the page data PD shown in FIG. 12A, the page data shaping unit 113 creates the file name "exptag.txt" by the <GETINFO> tag shown in FIG. 12B and the file name "contents.txt" by the <IC_INDEX> tag shown in FIG. 12C.

The <COUPON> tag and the </COUPON> tag indicate the coupon information in the page data PD. Coupon information for

providing price discount or service in restaurants, tailor's, mass merchandise outlets, for example, has been conventionally distributed by a paper sheet ticket as a medium. When coupon information is distributed using a network such as the Internet, the coupon information is transmitted to the mobile terminal 30, and the coupon information may be verified at a restaurant, for example. The <COUPON> tag and the </COUPON> tag provide the coupon information in the page data PD.

In the page data PD shown in FIG. 13, the page data shaping unit 113 recognizes the range delimited by the <COUPON> tag and the </COUPON> tag as the coupon information. Like the <GETINFO> tag, the <COUPON> tag permits a "name" parameter and a "link" parameter to be designated. Further, the <COUPON> tag designates a "limit" parameter. The "limit" parameter indicates the expiration date of the content of the coupon information.

In accordance with the designated identifier STG, the page data shaping unit 113 analyzes the page data PD for the acquired area, the unnecessary area, the file name, and the coupon information, and then shapes the transmission data TD. Using the designated identifier STG, the page data shaping unit 113 efficiently and quickly shapes the page data PD. Based on the designated identifier STG, the page data shaping unit 113 imparts new additional information, such as an expiration date and a file name of the shaped data file to the shaped data. For example,

when the file shaped by the user is the coupon information, the data may be organized so that the user easily recognizes when it comes the expiration date.

It is possible to dynamically impart information to the page data PD, for example, of how many days the information remains effective from when the user acquired the page data PD. The information provider has more freedom of information added to the page data PD. Now, described in the page data PD is a designated identifier for imparting additional information using information prestored and set in the information processing apparatus 20, namely, the user computer. The additional information is imparted according to the information prestored and set in the user computer. Information is thus dynamically imparted.

For example, map information is now stored. By simply designating latitude and longitude by the designated identifier STG or the parameters thereof, the geographic position on the map is determined. The page data PD may include a designated identifier STG for creating a map file detailing a geographical area in and around the designated latitude and longitude for the user. The page data PD may include a designated identifier STG for adding to the shaped data, the data of the user name, user information, the age and sex of the user already registered in the user computer. By using the designated identifier STG in this way, not only the information provided by the service but

also the user's individual additional information are added to the shaped data.

The page data PD may provide particular information such as the coupon information. As for the coupon information, the tags of the page data PD may not be sufficient enough to convey the expiration date. By allowing the page data shaping unit 113 to analyze the designated identifier STG and the parameters thereof, the user may use the coupon information provided by the page data PD in substantially the same intervals as the coupon information provided by an actual paper sheet coupon ticket.

The page data shaping unit 113 converts image data of various formats for instance, JPEG (Joint Photographic Coding Experts Group) or GIF (Graphics Interchange Format) into black and white binary bitmap data. The data converter 101 may convert the image data into the black and white binary bitmap data using a pattern method, a cluster method, or a dithering method. The page data acquisition unit 112 aligns the text document while adjusting the size of the image data.

In this way, the page data shaping unit 113 has the function of shaping the page data PD, such as analyzing, extracting, converting, and aligning the page data PD. The data converter 101 creates a directory (a folder) in the transmission data area 103, and stores the converted transmission data TD in that directory.

FIG. 14 shows a main window 130 of the information

processing apparatus 20 of the present invention. The user operates the information processing apparatus 20 observing the main window 130. The main window 130 is presented on the display device 25 at the startup of an information processing program.

The main window 130 of the information processing apparatus 20 shown in FIG. 14 includes a title bar 131, a menu bar 132, a tool bar 133, a transmission data window AR 8, a preview window AR 9, a mobile terminal window AR 10, etc.

The title bar 131 displays a window name K251 and an icon S251. The menu bar 132 is used to execute commands for shaping and transmitting the page data PD, and settings for the information processing apparatus 20. The tool bar 133 presents icons of frequently used commands registered in the menu bar 132. By clicking an icon, the respective process is executed.

The tool bar 133 presents a conversion icon CA and a service icon SA. When the conversion icon CA is clicked, the data converter 101 shown in FIG. 6 starts up, performing a conversion operation. The service icon SA is formed for each server, and each service icon SA is assigned with a service identifier 403 shown in FIG. 7A. In response to the clicking of the service icon SA, the service identifier 403 is sent to the processing controller 111 shown in FIG. 6. The processing controller 111 starts up, thereby extracting the processing condition data PCD in accordance with the service identifier 403.

The transmission data window AR 8 displays the content of

the transmission data area 103, namely, the transmission data TD in a tree structure. By selecting a predetermined file in the transmission data window AR 8 with a cursor, the selected file is transmitted and displayed on the preview screen. The transmission data window AR 8 includes, on the upper portion thereof, a memory window AR 8a for displaying the capacity of the storage unit 96 in the mobile terminal 30 and the size of the transmission data TD stored in the transmission data area 103. Monitoring the memory window AR 8a, the user transmits data to the mobile terminal 30. The user can thus adjust the number and file size of the transmission data TD transmitted to the mobile terminal 30.

The preview window AR 9, formed below the transmission data window AR 8, displays the transmission data TD selected in the transmission data window AR 8. When a text file is selected in the transmission data window AR 8, the preview window AR 9 displays a text document. When a bitmap file is selected, the preview window AR 9 displays a black and white binary image. The mobile terminal window AR 10 displays the front view of the mobile terminal 30 with the data shown in a tree structure on the screen of the mobile terminal 30.

The mobile terminal window AR 10 displays a transmission icon Y0. The transmission icon Y0 includes an arrow Y1 pointing from the transmission data window AR 8 to the mobile terminal window AR 10 and an arrow Y2 pointing from the mobile terminal

window AR 10 to the transmission data window AR 8. When the transmission icon Y0 is clicked, the transmission unit 102 shown in FIG. 6 starts up, sending the transmission data TD to the mobile terminal 30. Specifically, when the arrow Y1 is clicked, the transmission data TD is sent from the transmission data area 103 to the mobile terminal 30. When the arrow Y2 is clicked, the transmission data TD is sent from the mobile terminal 30 to the transmission data area 103.

FIG. 15 is a flow diagram showing a preferred embodiment of the information processing method of the present invention.

The information processing method is now discussed, referring to FIG. 15. In step ST1, the user manipulates the mouse to click the service icon SA shown in FIG. 14. In step ST2, the processing controller 111 shown in FIG. 6 receives the service identifier 403 assigned to each service icon SA.

In step ST3, the processing controller 111 reads the processing condition data PCD of the service identifier 403 received from the processing condition data area 114. In step ST4, the processing controller 111 displays the acquired icon AA on the display device 25 using the image of the service identifier 403 in the processing condition data PCD. The processing controller 111 starts up the file monitor 200, sending the address information 407 of the processing condition data PCD to the file monitor 200.

Referring to FIG. 16, the display device 25 displays, on

the screen thereof, the file monitor 200 with the page data PD of the address information 407 of the processing condition data PCD presented thereon, and the acquired icon AA. The page data PD presented on the file monitor 200 can be an index page, i.e., the top page of the database accessible on the network server.

Referring to FIG. 17, a procedure from the acquisition of the page data PD to the shaping of the page data PD is now discussed.

In step ST10, monitoring the page data PD, the user operates the file monitor 200 so that the file monitor 200 presents the desired page data PD to be displayed, namely, the page data PD to be transmitted to the mobile terminal 30. In step ST11, the user clicks the acquired icon AA when the target page data PD is displayed on the file monitor 200. In response to the clicking of the acquired icon AA, the page data acquisition unit 112 starts up.

In step S12, the page data acquisition unit 112 shown in FIG. 6 acquires the address AS such as the URL from the file monitor 200. In step S13, the page data acquisition unit 112 searches for the data file of the page data PD currently being observed, based on the address AS. The page data acquisition unit 112 searches for the corresponding page data PD from among the page data PD stored in the cache area 201 in the file monitor 200. The page data acquisition unit 112 sends the acquired page data PD to the page data shaping unit 113.

In this way, the acquisition of the page data PD is performed

in an off-line state without connecting to a network. This method eliminates a step for connecting to the network, and results in costs lower than those when a telephone line is used.

In step ST14, the page data shaping unit 113 creates a directory in the transmission data area 103, based on the directory information of the processing condition data PCD.

Used as the name of the directory is the service name shown in FIG. 7A. A file corresponding to each service is stored in the directory created according to the type of service in the transmission data area 103. A file searching in the transmission data TD having a tree structure becomes easy, and user interface is improved.

The page data shaping unit 113 recognizes the designated identifier STG of the acquired page data PD, extracts the data from the page data PD, and analyzes the tag in the extracted data according to the tag analysis conditions 408b shown in FIG. 7B.

The page data shaping unit 113 thus produces a text file and a bitmap file. Specifically, as shown in FIG. 18, a current buffer to be used for character string processing is initialized in step ST101. In step ST102, a check is made to determine whether the character string forming the page data PD includes a designated identifier STG. When it is determined that the character string forming the page data PD includes a designated identifier STG, steps in ST103, ST104, ST105, and ST106 are respectively performed in accordance with the type of the

designated identifier STG. When no designated identifier STG is included, the character string of the page data PD is stored in the current buffer. The character string of the page data PD within the range delimited by the designated identifiers STG is also stored in the current buffer. Steps ST102-ST108 are performed on all character strings of the page data PD.

FIG. 19 is a flow diagram showing the processing method of the <DUMPINFO> tag and the </DUMPINFO> tag as the designated identifiers STG. In step ST111 in FIG. 19, it is determined whether a tag recognized by the page data shaping unit 113 is a <DUMPINFO> tag. When it is determined that the <DUMPINFO> tag is recognized, the content of the current buffer is stored in a second buffer for character string processing in step ST112. The data stored in the current buffer is thus protected during the processing of character strings. In steps ST102-ST108 in FIG. 18, the character data following the <DUMPINFO> tag is stored in the current buffer.

If a </DUMPINFO> tag is recognized in the page data PD in step ST113, all data stored in the current buffer is erased in step ST114. The data within the range delimited by the <DUMPINFO> tag and the </DUMPINFO> tag is deleted. In step ST115, the data evacuated in the second buffer is moved to the current buffer.

FIG. 20 is a flow diagram showing the processing method of the <IC_INDEX> tag and the </IC_INDEX> tag as the designated

identifiers STG. In step ST121 in FIG. 20, it is determined whether a tag recognized by the page data shaping unit 113 is a <IC_INDEX> tag. When it determined that the <IC_INDEX> tag is recognized, the content of the current buffer is stored in a second buffer for character string processing in step ST122.

The data stored in the current buffer is thus protected during the processing of character strings. In step S123, a "name" parameter and a "link" parameter designated in the <IC_INDEX> tag are recognized. In steps ST102-ST108 in FIG. 18, the character data following the <IC_INDEX> tag is stored in the current buffer.

If a </IC_INDEX> tag is recognized in the page data PD in step ST124, the page data shaping unit 113 regards the content of the current buffer and the parameter as the data to be shaped, and reads the data stored in the current buffer in step ST125.

In step ST126, the data stored in the second buffer is moved to the current buffer.

FIG. 21 is a flow diagram showing the processing method of the <COUPON> tag and the </COUPON> tag as the designated identifiers STG. In step ST131 in FIG. 21, it is determined whether a tag recognized by the page data shaping unit 113 is a <COUPON> tag. When it determined that the <COUPON> tag is recognized, the content of the current buffer is stored in a second buffer for character string processing in step ST132. The data stored in the current buffer is thus protected during the

acquisition area.

In the above discussion, the mobile terminal 30 handles the text data and the bitmap data as the data format of the transmission data TD. Another data format is acceptable as long as the mobile terminal 30 can handle.

In accordance with the present invention, the page data is processed to be displayable on the mobile terminal according to the designated identifier and processing information data. The present invention thus provides the information processing apparatus, and the information processing method having good user interface capability, and a program storage medium for storing the information processing program.

processing of character strings. In step S133, a "limit" parameter designated in the <COUPON> tag are recognized. In steps ST102-ST108 in FIG. 18, the character data following the <COUPON> tag is stored in the current buffer.

If a </COUPON> tag is recognized in the page data PD in step ST134, the page data shaping unit 113 regards the content of the current buffer and the parameter as the data to be shaped, and reads the data stored in the current buffer in step ST135. In step ST136, the current buffer restores the data thereof, with the data stored in the second buffer moved thereto.

FIG. 22 is a flow diagram showing the processing method of the <GETINFO> tag and the </GETINFO> tag as the designated identifiers STG. In step ST141 in FIG. 22, it is determined whether a tag recognized by the page data shaping unit 113 is a <GETINFO> tag. When it determined that the <GETINFO> tag is recognized, the content of the current buffer is stored in a second buffer for character string processing in step ST142 for evacuation. The data stored in the current buffer is thus protected during the processing of character strings. In step S143, a "name" parameter and a "link" parameter designated in the <GETINFO> tag are recognized. In steps ST102-ST108 in FIG. 18, the character data following the <GETINFO> tag is newly stored in the current buffer.

If a </GETINFO> tag is recognized in the page data PD in step ST144, the page data shaping unit 113 regards the content

of the current buffer and the parameter as the data to be shaped, and retrieves the data stored in the current buffer in step ST145.

In step ST146, the current buffer restores the data thereof, with the data stored in the second buffer moved thereto.

In this way, the page data shaping unit 113 recognizes the designated identifiers STG and extracts, from the page data PD, the data to be shaped. The page data shaping unit 113 shapes the page data PD to be displayable on the mobile terminal 30 based on the processing condition data PCD. Specifically, the processing condition data PCD shown in FIG. 23 is now acquired and shaped. For example, first page data PD1 of the page data PD is associated with the <COUPON> tag and the </COUPON> tag, and second page data PD3 is associated with the <IC_INDEX> tag and the </IC_INDEX> tag. The page data shaping unit 113 extracts the first acquired page data PD1 and the second acquired page data PD3.

The page data shaping unit 113 analyzes the first acquired page data PD1 and the second acquired page data PD3 according to the tag analysis conditions 408b. The page data shaping unit 113 converts the first acquired page data PD1 and the second acquired page data PD3 into text files TEXT1 and TEXT2 according to the tag analysis conditions 408b. Further, the page data shaping unit 113 performs a character count per line process and a line boundary character process on the text files TEXT1 and TEXT2 according to the format conditions 408a.

On the other hand, the page data shaping unit 113 extracts acquired image data PD2 as an image file within the page data PD to be converted, according to the file condition in the shaping conditions 408a. The page data shaping unit 113 converts the data format of the acquired image data PD2 compatible with GIF, JPEG, or the like into a bitmap file BMP1. The page data shaping unit 113 adjusts the converted bitmap file BMP1 in file size, file height, width according to the imaging conditions 408c.

Referring to FIGS. 24A, 24B, and 24C, the mobile terminal 30 presents the text files TEXT1 (FIG. 24B), and TEXT2 (FIG. 24C), and the image file BMP1 (FIG. 24A) in their proper state. Since the page data shaping unit 113 shapes the data according to the shaping conditions 408, the user performs the acquisition and shaping process by simply clicking the acquired icon AA. The acquisition and shaping process is thus efficiently performed.

In step ST15 shown in FIG. 17, the page data shaping unit 113 stores the created transmission data TD in the transmission data area 103. In this case, the page data shaping unit 113 holds the transmission data TD in directories (folders) created in the transmission data area 103. Referring to FIG. 25, the transmission data window AR 8 displays the text file and the bitmap file, created by the page data shaping unit 113, in their state held in the directories. The user selects a file in the transmission data window AR 8, or transmits the transmission data TD to the mobile terminal 30 in a bulk.

In each of the above embodiments, the page data shaping unit 113 extracts the necessary data from the page data PD in accordance with the designated identifier attached to the page data PD, and shapes the extracted data according the processing condition data PCD. The shaping operation of the data is efficiently and quickly performed. With the designated identifier attached, the data within the page data has a particular meaning. Specifically, by attaching the coupon identifier indicating the coupon information, for example, the coupon service may be provided over the Internet.

The present invention is not limited to the above embodiments. In the above discussion, the page data PD is located on the network. The present invention is applicable to a HTML document in the form of a manual distributed on a CD-ROM or a floppy disk. In this case, the address AS presented on the file monitor 200 is the location of the corresponding file in the auxiliary storage device 23. The page data PD may be stored in the hard disk when the information processing apparatus 20 is shipped. In this case, the address AS presented in the file monitor 200 is the location of the corresponding file in the auxiliary storage device 23. The page data acquisition unit 112 shown in FIG. 6 may have an acquisition area for separately storing another page data PD. The page data acquisition unit 112 may directly access the page data PD on the network in accordance with the address AS and store the page data PD on the